



NOTES:

1. BPOD = BARRELS PER OPERATING DRY AT 60°F
 SCFH = STANDARD CUBIC FEET PER HOUR AT 60°F AND 14.7 PSIA
 GPM = GALLONS PER MINUTE AT FLOW CONDITIONS
 DES. = DESIGN RATE
2.
 - VALVE NORMALLY OPEN
 - VALVE NORMALLY CLOSED
 - CONTROL VALVE
 - GLOBE VALVE
 - MIXING VALVE

REFERENCE DRAWINGS:

- RF 844700 - PROCESS FLOW DIAGRAM - PLANTS 11 AND 21 - DEA ABSORBERS AND REGENERATION
- RF 844701 - PROCESS FLOW DIAGRAM - PLANTS 11 AND 21 - AMINE FILTRATION
- RF 845474 - PROCESS FLOW DIAGRAM - PLANTS 15 AND 25 - TRAIL GAS
- RF 844503 - PROCESS FLOW DIAGRAM - PLANT 16 - FRACTIONATION

REVISION		SCALE	DATE
		NONE	10/24/84

CHEVRON RESEARCH COMPANY
 PROCESS ENGINEERING DEPT.
 PROCESS DESIGN DIVISION

SIMPLIFIED PROCESS FLOW DIAGRAM
 PLANT 17 - LIQUID TREATING SECTION
 GAVIOTA GAS PLANT
 NO. 30044 RF 844191 REVISION

CONFIDENTIAL
 PROPERTY OF CHEVRON RESEARCH COMPANY.
 TO BE REPRODUCED AND USED ONLY IN
 ACCORDANCE WITH WRITTEN PERMISSION OF
 CHEVRON RESEARCH COMPANY